

**AIROSOL COMPANY, INC.**  
**MCKAY CHEMICALS** **MECHANICS BRAND**  
1101 Illinois, PO Box 120, Neodesha KS 66757 - Phone 620-325-2666

**MATERIAL SAFETY DATA SHEET**

PRODUCT NAME: **McKAY Power Steering Fluid with Stop Leak**  
PRODUCT CODE: **50507**

**SECTION I - MANUFACTURER IDENTIFICATION**

MANUFACTURER'S NAME: Airosol Company, Inc.  
ADDRESS: PO Box 120, Neodesha KS 66757  
EMERGENCY PHONE: 1-800-535-5053  
INFORMATION PHONE: 1-800-633-9576  
DATE REVISED: 11/4/2005, Revised 3/26/2009

**SECTION 2 - COMPOSITION /INFORMATION ON INGREDIENTS**

COMPONENTS	CAS NUMBER	AMOUNT
Distillates, Hydrotreated, Heavy Paffarrinic	64741-88-4 64741-89-5	93.00-99.00 %Weight
Additives	Mixture	1.00-7.00 %Weight

The BASE OIL may be a mixture of the following: CAS 64741884, CAS 64741895, CAS 64741964, CAS 64741975, CAS 64742014, CAS 64742525, CAS 64742536, CAS 64742547, CAS 64742558, CAS 64742570, CAS 64742627.

The ADDITIVES are a mixture of confidential ingredients permitted by 29 CFR 1910.1200 and various State Right to Know Laws. IN the event of medical emergency, specific chemical information will be disclosed to a treating physician or nurse.

**SECTION 3 - HAZARD IDENTIFICATION**

**IMMEDIATE HEALTH EFFECTS**

**Eye:** Not expected to cause prolonged or significant eye irritation.

**Skin:** Contact with the skin is not expected to cause prolonged or significant irritation. Not expected to be harmful to internal organs if absorbed through the skin.

**Ingestion:** Not expected to be harmful if swallowed.

**Inhalation:** Not expected to be harmful if inhaled. Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

**SECTION 4 - FIRST AID MEASURES**

**Eye:** No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

**Skin:** No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

**Ingestion:** No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

**Inhalation:** No specific first aid measures are required. If exposed to excess levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

**SECTION 5 - FIRE FIGHTING MEASURES**

**FIRE CLASSIFICATION**

OSHA Classification (29 CFR 1910.1200): Not classified by OSHA as flammable or combustible.

**NFPA RATINGS:** Health: 0 Flammability: 1 Reactivity: 0

**FLAMMABLE PROPERTIES:**

**Flashpoint:** 175 °F (347 °C) (Min)

**Autoignition:** NDA

Flammability (Explosive) Limit (%by volume in air): Lower: NA Upper: NA

PRODUCT NAME:	<b>McKAY Power Steering Fluid with Stop Leak</b>
PRODUCT CODE:	<b>50507</b>

## SECTION 5 - FIRE FIGHTING MEASURES (CONTINUED)

### EXTINGUISHING MEDIA:

Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

### PROTECTION OF FIRE FIGHTERS:

**Fire Fighting Instructions:** This material will burn although it is not easily ignited. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

**Combustion Products:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of: Sulfur, Phosphorus.

## SECTION 6 - ACCIDENTAL RELEASE INFORMATION

**Protective Measures:** Eliminate all sources of ignition in vicinity of spilled material.

**Spill Management:** Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

**Reporting:** Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at (800) 424-8802 as appropriate or required.

## SECTION 7 – HANDLING AND STORAGE

**Precautionary Measures:** DO NOT USE IN HIGH PRESSURE SYSTEMS in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed. Keep out of reach of children

**General Handling Information:** Avoid Contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

**Static Hazard:** Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating an accumulation of electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids', National Fire Protection Association (NFPA 77, 'Recommended Practice or Static Electricity', and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents'.

**Container Warnings:** Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum conditioner or disposed of properly.

## SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTIVE EQUIPMENT

### GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section III), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Special Note: Do not use in breathing air apparatus or medical equipment.

### ENGINEERING CONTROLS:

Use in a well-ventilated area.

### PERSONAL PROTECTIVE EQUIPMENT:

**Eye/Face Protection:** No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

**Skin Protection:** No special protective clothing is normally required. Where splashing is possible, select protective clothing depending on operations conducted, physical requirements and other substances in the workplace. Suggested materials for protective gloves include: 4H (PE/EVAL), Nitrile Rubber, Silver Shield, Viton.

PRODUCT NAME:	<b>McKAY Power Steering Fluid with Stop Leak</b>
PRODUCT CODE:	<b>50507</b>

## SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTIVE EQUIPMENT (CONTINUED)

**Respiratory Protection:** No respiratory protection is normally required.

If user operations generate an oil mist, determine if airborne concentrations are below occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from measured concentrations of this material. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

### Occupational Exposure Limits:

Component	Agency	TWA	STEL	Ceiling	Notation
Highly refined mineral oil (C15-C50)	ACGIH	5mg/m3	10mg/m3		
Highly refined mineral oil (C15-C50)	OSHA_PEL	5mg/m3			

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

**Appearance and Odor:** Red oily liquid.

**PH:** NA

**Vapor Pressure:** <0.01 mmHg @ 100 °F

**Vapor Density (Air=1):** >1

**Boiling Point:** 600 °F (315 C)(Min)

**Solubility:** Soluble in hydrocarbons; insoluble in water

**Freezing Point:** NA

**Melting Point:** NA

**Specific Gravity:** 0.85 @ 15.6 °C/15.6 °C

**Viscosity:** 34.1 cSt @ 40 °C (104 °F)

## SECTION 10 - STABILITY AND REACTIVITY

**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Incompatibility with Other Materials:** May react with strong oxidizing agents, such as chlorates, nitrates, and peroxides, etc.

**Hazardous Decomposition Products:** Hydrogen Sulfide (Temperatures >149 °F (65 °C))

**Hazardous Polymerization:** Hazardous polymerization will not occur.

## SECTION 11 – TOXICOLOGICAL INFORMATION

### IMMEDIATE HEALTH EFFECTS:

**Eye Irritation:** The eye irritation hazard is based on evaluation of data similar for materials of product components.

**Skin Irritation:** The skin irritation hazard is based on evaluation of data for similar materials of product components.

**Skin Sensitization:** No product toxicology data available.

**Acute Dermal Toxicity:** The acute dermal toxicity hazard is based on evaluation of data similar materials or product components.

**Acute Oral Toxicity:** The acute oral toxicity hazard is based on evaluation of data similar materials or product components.

**Acute Inhalation Toxicity:** The acute inhalation toxicity hazard is based on evaluation of data similar materials or product components.

### ADDITIONAL TOXICOLOGY INFORMATION:

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possible carcinogenic to humans (Group 2B). These oils have not been classified by the American Conference of Government Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

During use in engines, contamination of oil with low levels of cancer-causing combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

PRODUCT NAME:	<b>McKAY Power Steering Fluid with Stop Leak</b>
PRODUCT CODE:	<b>50507</b>

## SECTION 12 – ECOLOGICAL INFORMATION

### EXOTOXICITY

The toxicity of the material to aquatic organisms has not been evaluated. Consequently, the material should be kept out of sewage and drainage systems and all bodies of water

### ENVIRONMENTAL FATE

This material is not expected to be readily biodegradable.

## SECTION 13 –DISPOSAL INFORMATION

Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods. (see B.C Reg. GY/92 Waste Management Act; R.R.O. 1990, Reg. 347 General-Waste Management; C.CSM.c. W40 The Waste Reduction and Prevention Act; N.S. Reg. 51/95 and N.S. Reg. 179/96 for examples of Provincial legislation.)

## SECTION 14 – TRANSPORTATION INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g. technical name) and mode-specific or quantity-specific shipping requirements.

**DOT Shipping Name:** Not regulated as a hazardous material for transportation under 49CFR

**DOT Hazard Class:** Not Applicable

**DOT Identification Number:** Not Applicable

**DOT Packing Group:** Not Applicable

**Additional Information:** Not hazardous by U.S. DOT ADR/RID hazard class not applicable

**IMO/IMDG Shipping Name:** Not regulated as dangerous goods for transportation under the IMDG Code

**IMO/IMDG Hazard Class:** Not Applicable

**IMO/IMDG Identification Number:** Not Applicable

**IMO/IMDG Packing Group:** Not Applicable

## SECTION 15 – REGULATORY INFORMATION

<b>EPCRA 311/312 Categories:</b>	1. Immediate (Acute) Health Effects:	NO
	2. Delayed (Chronic) Health Effects:	NO
	3. Fire Hazard:	NO
	4. Sudden Release of Pressure Hazard:	NO
	5. Reactivity Hazard:	NO

Regulatory Lists Searched:

4_I1=IARC Group 1	15=SARA Section 313
4_I2A=IARC Group 2A	16=CA Proposition 65
4_I2B=IARC Group 2B	17=MA RTK
05=NTP Carcinogen	18=NJ RTK
06=OSHA Cardinogen	19=DOT Marine Pollutant
09=TSCA 12(b)	20=PA RTK

### CHEMICAL INVENTORIES:

**AUSTRALIA:** This material contains components that require notification before sale or importation into Australia.

**CANADA:** One or more components of this product are not on the Domestic Substances List (DSL). Volume tracking or notification by the Canadian Importer of Record may be required.

**EUROPEAN UNION:** All the components of this material are in compliance with the EU Seventh Amendment Directive 92/32/EEC.

**JAPAN:** This material may contain components that require notification before sale or importation into Japan.

**KOREA:** This material may contain components that require notification before sale or importation into Korea.

**PHILIPPINES:** This material may contain components that require notification before sale or importation into the Philippines.

**UNITED STATES:** All of the components of this material are on the Toxic Substance Control Act (TSCA) Chemical Inventory

### NEW JERSEY RTK CLASSIFICATION:

Under the New Jersey Right-to-Know Act L.1983 Chaper 315 N.J.S.A. 34:5A-1 et.seq., the product is to be identified as as follows:

PETROLEUM OIL (Automatic Transmission Fluid)

### WHMIS CLASSIFICATION:

This product is not considered a controlled product according to the criteria of the Canadian Controlled Products Regulations.

PRODUCT NAME:	<b>McKAY Power Steering Fluid with Stop Leak</b>
PRODUCT CODE:	<b>50507</b>

### SECTION 16 - DISCLAIMER

**NFPA RATINGS:** Health: 0 Flammability: 1 Reactivity: 0

**HMIS RATINGS:** Health: 1 Flammability: 1 Reactivity: 0

(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:-Personal Protection Equipment Index recommendation,\*-Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

**REVISION STATEMENT:** Revision updates many sections and the MSDS should be read in its entirety.

**ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:**

TLV – Threshold Limit Value	TWA – Time Weighted Average
STEL – Short-term Exposure Limit	PEL – Permissible Exposure Limit
CHA – Champion LLC	CAS – Chemical Abstract Service Number
NDA – No Data Available	NA – Not Applicable
<= - Less than or equal to	>= - Greater than or equal to

Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the ANSI MSDS Standard (z400.1)

**DISCLAIMER:** The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or to be implied regarding the accuracy or completeness of this information or the product, the safety of this product, or the hazards related to its use. This information and product are furnished "as is" and on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use thereof.